


Computer Graphics II: Rendering

CSE 168[Spr 20],Lecture 9: Importance Sampling
Ravi Ramamoorthi

<http://viscomp.ucsd.edu/classes/cse168/sp20>



To Do


- Start working on homework 3. Ask me if problems
- Also homework 4. This lecture covers material (Lecture is designed to follow assignment closely)
- Start thinking about final project

Importance Sampling

- Talked about in Monte Carlo Path Tracing
- This assignment: implement at each bounce
- Use “good” pdf for sampling instead of uniform
- Extension to Multiple Importance Sampling (Veach 95)
 - Allows considering both lighting and BRDF sampling
 - Key development in production rendering (Academy Award)
 - Remains active topic of research (many papers in 2019)

Sampling Projected Solid Angle

Generate cosine weighted distribution



CS348B Lecture 6

Pat Hanrahan, Spring 2004

Cosine Importance Sampling



- Include cosine term in PDF (for indirect lighting)
- Previously, uniformly integrate over hemisphere $\text{pdf}(\omega) = \frac{1}{2\pi}$
- Now, consider a cosine PDF $\text{pdf}(\omega) = \frac{n \cdot \omega}{\pi}$

$$\frac{1}{N} \sum_{k=1}^N \frac{L(\omega_{ik}) f(\omega_{ik}, \omega_o) (n \cdot \omega_{ik})}{\text{pdf}(\omega_i)} = \frac{2\pi}{N} \sum_{k=1}^N L(\omega_{ik}) f(\omega_{ik}, \omega_o) (n \cdot \omega_{ik})$$

$$\frac{1}{N} \sum_{k=1}^N \frac{L(\omega_{ik}) f(\omega_{ik}, \omega_o) (n \cdot \omega_{ik})}{\text{pdf}(\omega_i)} = \frac{\pi}{N} \sum_{k=1}^N L(\omega_{ik}) f(\omega_{ik}, \omega_o) = \frac{\pi}{N} \sum_{k=1}^N L(\omega_{ik}) f(\omega_{ik}, \omega_o)$$

Cosine Sampling Upper Hemisphere

- Inversion method
 - In polar coords, density must be proportional to $\cos \theta \sin \theta$ (remember $d(\text{solid angle}) = \sin \theta d\theta d\phi$)
 - Integrate, invert $\rightarrow \cos^{-1}(\sqrt{r})$
- Recipe is (start with two random numbers ξ_1, ξ_2 in 0...1)
 - Generate ϕ in $0..2\pi$ $\phi = 2\pi\xi_2$
 - Generate z in $0..1$ $z = \sqrt{\xi_1}$ // Note extra sqrt wrt uniform
 - Let $\theta = \cos^{-1} z$ $\theta = \arccos(z) = \arccos(\sqrt{\xi_1})$
 - $(x, y, z) = (\sin \theta \cos \phi, \sin \theta \sin \phi, \cos \theta)$
- Rotate according to surface normal (z goes to normal)
 - Or create coordinate frame (as you did for uniform sampling)
- Modify indirect lighting estimator (remove $n \cdot \omega_i$) and replace 2π with π (indirect lighting, Russian Roulette)



Specular BRDFs

- Cosine importance sampling works well for near-Lambertian BRDFs (modest improvement)
- But more sophisticated sampling for specular BRDFs
- Will talk about general BRDFs next lecture
- For now, for assignment: Modified Phong, GGX
- Sampling BRDFs in general is non-trivial
 - Can simply normalize to get PDF, but sampling non-trivial
 - For now, sample a simpler BRDF, then divide by PDF
 - (This procedure is always guaranteed to work)

BRDF Importance Sampling

- Phong BRDF: $f_r \sim \cos^s \beta$ where β is angle between outgoing ray and ideal mirror direction
- Constant scale = $k_s(s+2)/(2\pi)$
- Can't sample this times $\cos \theta_i$
 - Can only sample BRDF itself, then multiply by $\cos \theta_i$
 - That's OK – still better than random sampling



BRDF Importance Sampling

- Recipe for sampling specular term:
 - Generate z in $0..1$
 - Let $y = \cos^{-1}(z^{1/(s+1)})$
 - Generate ϕ_y in $0..2\pi$
 - This gives direction w.r.t. ideal mirror direction
- Convert to (x,y,z) , then rotate such that z points along mirror dir.

Formal Modified Phong Sampling

- Multiply by cosine, transport function (note colors)
- Modified Phong is an approximation
$$t = \frac{\bar{k}_s}{\bar{k}_d + \bar{k}_s}$$

$$(1-t) \frac{n \cdot \omega_i}{\pi} + t \frac{s+1}{2\pi} (r \cdot \omega_i)^s$$
- Generate 3 random numbers: ξ_0, ξ_1, ξ_2 in $0..1$
- Use ξ_0 to decide diffuse ($>t$) or specular ($\leq t$)
- Generate ϕ in $0..2\pi$ $\phi = 2\pi \xi_2$
- If diffuse $\theta = \arccos(\sqrt{\xi_1})$ [coord. frame normal n]
- If specular $\theta = \arccos(\xi_1^{1/(s+1)})$ [coord. frame refl r]
- Compute BRDF / PDF (if below visible, BRDF = 0)



GGX Microfacet Model

- Physically-Based Reflectance Model
- Widely used in practice
- Will discuss BRDFs in more detail next time
- Brief review here, see assignment for details

Experiment

Reflections from a shiny floor

From Lafontaine, Foo, Torrance, Greenberg, SIGGRAPH 97

Reflection is greater at glancing angles

Fresnel Reflectance







Schlick Approximation $F(\theta) = F(0) + (1 - F(0))(1 - \cos\theta)^5$


(Cook-)Torrance-Sparrow

- Assume the surface is made up of grooves at the microscopic level. (General Microfacet Theory)

- Assume the faces of these grooves (called microfacets) are perfect reflectors.
- Take into account 3 phenomena

Shadowing Masking Interreflection





Multiple Importance Sampling

- MIS relies on NEE almost everywhere, but relies on BRDF importance sampling when needed
- Multi-sample: sample both distributions at each intersection
- General case: N sampling techniques (inner summation is unbiased estimator each technique)

$$\int_X f(x) dx \approx \sum_{i=1}^N \frac{1}{N_i} \sum_{j=1}^{N_i} w_i(x_j) \frac{f(x_j)}{pdf_i(x_j)}$$

- Weights must sum to 1, unbiased

Multiple Importance Sampling

- General case: N sampling techniques (inner summation is unbiased estimator each technique)

$$\int_X f(x) dx \approx \sum_{i=1}^N \frac{1}{N_i} \sum_{j=1}^{N_i} w_i(x_j) \frac{f(x_j)}{pdf_i(x_j)}$$
- Weights must sum to 1, unbiased
 - Interesting theory (ongoing, papers in 2019)
 - Veach and Guibas 95 proposed balance, power heuristics (provably “good” under certain assumptions)
 - We use power heuristic with $\beta = 2$
 - Subtle point: PDF must be able to be evaluated anywhere (not just own samples)
- Natural abstract interface for sampling and MIS
 - Eval(), Sample(), PDF() [sometimes Value() = Eval/PDF]

Lighting/BRDF Sampling

- For now, 1 sample on light (NEE), 1 from BRDF
 - We already know BRDF PDF
 - Light PDF implicitly on light, convert to angle $d\omega = dA \frac{\cos\theta}{R^2}$
- pdf_{light}(ω) = $\frac{R^2}{(\mathbf{n}_{light} \cdot \omega) A}$
- For multiple lights, simple normalization (see homework)
- Combine NEE and BRDF sampling (power heuristic)

$$w_i(\omega) = \frac{pdf_i^\beta(\omega)}{\sum_{k=1}^N pdf_k^\beta(\omega)}$$

MIS Implementation

- Can be tricky, see assignment
- First disable NEE, BRDF sampling for direct
 - Separate NEE function, toggle light/BRDF sampling
- Now implement pdf(nee)
 - Beware divide by zero, see assignment for specifics
- Implement weight function
 - Visualize weighted lighting, weighted BRDF
 - Then combine them with MIS, enable both techniques
- See assignment carefully
 - MIS for direct lighting only (Veach scene no indirect)
 - Note gamma correction for this assignment

MIS weights

Weighted contribution BRDF Importance

Weighted contribution of NEE